




Preventive Maintenance It Is About Money

Proven cost savings with the only product-line used
from nuclear submarines to the Space Shuttle. Why?
One word – Quality.



Inside
Rudders



Tugboat ✿ Workboat ✿ Barge ✿ Dredge ✿ Fishing Vessel ✿ Floating Drydocks

- Anchor Chains–Lockers–Windlass
- Wire–Rope–Winches
- Cranes–Hoists–Rails
- Spoons–Stabilizers
- Hawsers–Hatch Coamings
- Offshore Platform Mach. & Tools
- Equipment–Vehicles–On–Deck Cargo
- Container Guides
- Elevator Guide Rails
- Open Gears
- Cables & Electric Connectors
- Ballast Tanks
- Voids–Skegs
- Bilges–Keels
- Stern Tubes
- Pontoons
- Caissons
- Undersea Equipment
- Hatch Covers
- Water Tight Door Dogs
- Locks & Hinges
- Grey Water Tanks



NOTHING LASTS LONGER
Environmentally Friendlier
No Solvents

 **STOTTS**
Australian Agent
Unit 1, 19 Balook Drive
Beresfield NSW 2322
Phone 02 4966 8020
Fax 02 4966 8302
www.stottind.com.au

The only product-line used from nuclear submarines to the Space Shuttle.

**Available in liquid, gel, and grease forms. ✿ Penetrates to base metal and cable core.
Displaces rust. Where surfaces are heavily corroded acts as descaler.**

National stock numbers listed where applicable to type of FLUID FILM and container size.

Tank Coatings, Rudder, and Void Preservatives, Appendage Protection

FLUID FILM Liquid A

Applied by spray, flotation, fill and drain, or brush. Use as a descaler over heavily corroded surfaces. Up to 2 years service.

NSN-8030-01-387-1051	5-gal. pail (20 liter)
NSN-8030-01-386-3877	1-gal. 4/case

FLUID FILM Liquid AR (semi-liquid)

Applied by spray or brush over moderately corroded surfaces after removal of thick rust scale. Up to 3-5 years service.

NA	5-gal. pail (20 liter)
NSN-8030-01-381-7311	1-gal. 4/case

FLUID FILM Gel BW

Applied by spray or brush over rusted surfaces. Long term protection. Up to 3-10 years service; submersibles to 20 years.

NA	5-gal. pail (20 liter)
----	------------------------

FLUID FILM Gel BEW

Applied to external appendages and components by brush.

NSN-8030-01-381-3160	5-gal. pail (20 liter)
----------------------	------------------------

Wire Rope Dressings

FLUID FILM Liquid A

Applied by lubricator, glove, or dipping. Core penetration without lubricator.

NSN-8030-01-387-1051	5-gal. pail (20 liter)
NSN-8030-01-386-3877	1-gal. 4/case

FLUID FILM WRO-EP (extreme pressure)

Government specification Mil-G018458 (SH) applied by lubricator or glove.

NSN-9159-00-530-6814	35 lb. pail (15.5 kg)
----------------------	-----------------------

General Maintenance Aerosol/Non-Aerosol

FLUID FILM AS (aerosol)

NSN-8030-01-387-1131	11-3/4 oz. 12/case
----------------------	--------------------

FLUID FILM NAS (non-aerosol)

NSN-8030-01-381-6357	12 oz. 12/case
NSN-8030-01-386-3871	1-gal. 4/case
NSN-8030-01-387-1070	5-gal. pail (20 liter)